

## **AMENDMENT TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application. Please amend as follows:

1. (Cancelled)
2. (Cancelled)
3. (Cancelled)
4. (Cancelled)
5. (Cancelled)
6. (Cancelled)
7. (Original) A compressive pulp beating refiner comprising:  
a pulp in-feed;  
a refining zone for receiving the in-fed pulp, having two beating surfaces defined by confronting rolls; and  
a pulp outlet from the refining zone.
8. (Original) The compressive pulp beating refiner of claim 7, wherein said confronting rolls rotate at substantially the same rate.
9. (Previously Presented) The compressive pulp beating refiner of claim 7, wherein said confronting rolls rotate such that the beating surfaces of the rolls move at substantially the same speed.

10. (Original) The compressive pulp beating refiner of claim 7, wherein said confronting rolls rotate such that the beating surfaces of the rolls move at substantially the same speed while the confronting rolls rotate at a different rate.

11. (Previously Presented) The compressive pulp beating refiner of claim 7, wherein a pair of confronting rolls have opposed beating surfaces defining an extended beating gap.

12. (Original) The compressive pulp beating refiner of claim 11, wherein each roll utilizes a shoe-type support to form the extended gap.

13. (Original) The compressive pulp beating refiner of claim 11, wherein each roll utilizes a beam-type support to form the extended gap.

14. (Original) The compressive pulp beating refiner of claim 7, wherein both of said confronting rolls rotate and have interengagable spikes.

15. (Original) The compressive pulp beating refiner of claim 7, wherein both of said confronting rolls rotate and have fluting or grooves.

16. (Original) The compressive pulp beating refiner of claim 15, wherein said fluting or grooves extend in circumferential direction.

17. (Original) The compressive pulp beating refiner of claim 16, wherein said fluting or grooves angularly traverse a roll axis.

18. (Original) The compressive pulp beating refiner of claim 15, wherein said fluting or grooves engage one another.

19. (Original) The compressive pulp beating refiner of claim 15, wherein said fluting or grooves is trapezoidal in shape.

20. (Original) The compressive pulp beating refiner of claim 15, wherein said fluting or grooves have a base and the base has dewatering recesses.

21. (Original) The compressive pulp beating refiner of claim 15, wherein at least one roll surface has a pre-defined roughness.

22. (Original) The compressive pulp beating refiner of claim 7, wherein the in-feed includes a web guide feeding the pulp to a point directly in front of the beating zone.

23. (Original) The compressive pulp beating refiner of claim 7, wherein the in-feed is operatively connected to a pulp thickener.

24. (Original) The compressive pulp beating refiner of claim 7, wherein at least one beating surface is associated with a moving weave.

25. (Original) The compressive pulp beating refiner of claim 24, wherein the moving weave is wrapped round at least one roll.

26. (Original) The compressive pulp beating refiner of claim 24, wherein the moving weave is guided over deflection rolls and is pressure-loaded against at least one roll.

27. (Cancelled)

28. (New) A compressive pulp beating refiner comprising:  
a pulp in-feed;

a refining zone for receiving the in-fed pulp, having two beating surfaces defined by confronting rolls that directly contact and impose compressive and shear forces on the pulp to refine the pulp; and

a refined pulp outlet from the refining zone.

29. (New) The compressive pulp beating refiner of claim 28, wherein the confronting rolls have hard, non-smooth beating surfaces.